

**VP-100** 

Computer Graphics Video to RGB/HV/S Format Converter

| VGA/UXGA - 15-pin HD



The VP-100 is a high-performance format converter for computer graphics video signals. It converts a computer graphics video signal on a 15-pin HD connector to either RGBS, RGsB, or RGBHV video signals on BNC connectors

## **FEATURES**

High Bandwidth - 350MHz (-3dB)
Control - H/V sync shift & sync selection
Looping Input
Selectable Input Signal Termination
ID Bit Control
EQ (Peaking) Control
Active Line Amplification Circuitry



0.07%

## **TECHNICAL SPECIFICATIONS**

INPUT: 1 analog red, green, blue signals: 0.7Vpp/75Ω, H & V sync, TTL level, with loop on

15-pin HD (F) connectors

**OUTPUTS:** 1 analog red, green (with or without composite sync), blue signals:  $0.7 \text{ Vpp/}75\Omega$ ; H

& V syncs: TTL level (Hi-Z load) or analog level (75Ω load) on BNC connectors; 1

composite sync: TTL levels (Hi-Z load) or analog level (75Ω load)

VIDEO BANDWIDTH 350MHz

(-3dB):

DIFF. GAIN:

DIFF. PHASE: 0.03Deg

K-FACTOR: 0.05%

VIDEO S/N RATIO: 71dB

CONTROLS: Cable EQ, H & V sync shift, G/sync on green switch, Hs/Cs switch, ID bit switch,

input termination switch

EQ. CONTROL: 0 to +9.7dB @5MHz

**POWER** 

CONSUMPTION:

Power supply, mounting bracket

ACCESSORIES:

**INCLUDED** 

**OPTIONS:** 

RK-3T 19" rack adapter

12V DC, 60mA

**PRODUCT** 

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.3kg (0.6lbs) approx

**SHIPPING** 

23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.6kg (1.3lbs) approx

