



1633A Paired - Category 5 Unbonded-Pair Cable

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : Termination Instructions for Shielded UTP.pdf</p>
--	--

Description:

24 AWG solid bare copper conductors, non-plenum, Polyolefin insulation, twisted pairs, overall Beldfoil® Shield, drain wire, rip cord, see color code chart (below), PVC jacket (gray or blue).

SUITABLE APPLICATIONS:

Suitable Applications	Premise Horizontal Cable
-----------------------	--------------------------

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PO - Polyolefin
---------------------	-----------------

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	24
Outer Shield Drain Wire Stranding	Solid



1633A Paired - Category 5 Unbonded-Pair Cable

Outer Shield Drain Wire Conductor Material	TC - Tinned Copper
--	--------------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.260 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
Bulk Cable Weight	28 lbs/1000 ft.
Max. Recommended Pulling Tension	25 lbs.
Min. Bend Radius (Install)	1 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM, UL444
CEC/C(UL) Specification	CM
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
TIA/EIA Specification	568 TSB 36, Category 5
Other Specification	UL verified to TSB 36, Category 5

FLAME TEST:

UL Flame Test	UL1685 UL Loading
CSA Flame Test	FT1

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	330 pF/100 m
Nominal Velocity of Propagation	67 %
Maximum Delay (ns/100 m)	538 @ 100MHz ns/100 m
Maximum Delay Skew (ns/100m)	45 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9.38 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	5 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:



1633A Paired - Category 5 Unbonded-Pair Cable

Premise Cable Electricals :

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. Structural Return Loss (dB)	Fitted Impedance (Ohms)
1	2.0	62.3	No Spec	No Spec	100 ± 15%
4	4.1	53.3	No Spec	No Spec	100 ± 15%
8	5.8	48.8	No Spec	No Spec	100 ± 15%
10	6.5	47.3	No Spec	No Spec	100 ± 15%
16	8.2	44.3	No Spec	No Spec	100 ± 15%
20	9.3	42.8	No Spec	No Spec	100 ± 15%
25	10.4	41.3	No Spec	No Spec	100 ± 15%
31.25	11.7	39.9	No Spec	No Spec	100 ± 15%
62.5	17.0	35.4	No Spec	No Spec	100 ± 15%
100	22.0	32.3	No Spec	No Spec	100 ± 15%

NOTES:

Notes

Not compatible with RJ-11/12/45 telephone plugs. Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-TSB 36, Category 5.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1633A 0061000	4 TW PR FS PVC	1000	32	BLUE, LIGHT	C Z
1633A 006U1000	4 TW PR FS PVC	U1000	30	BLUE, LIGHT	Z
1633A F2V1000	4 TW PR FS PVC	1000	32	GRAY, DEC	C Z
1633A F2VU1000	4 TW PR FS PVC	U1000	30	GRAY, DEC	Z

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1

Revision Date: 02-21-2006

1633A Paired - Category 5 Unbonded-Pair Cable

© 2006 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.