HDS-720 Network AV Controller







Product Features

- IP Camera Control and Setting: set and save the preset points of BXB's HDC-713 IP Camera. Support the total of 1011 points (conference unit x 1009 + HOME + panorama view) and control the maximum of 16 cameras.
- Intuitive Web Interface: you can configure the system settings and control & monitor the camera's images on the web browser via the PC or mobile devices.
- Extensive Functions for Image Display: operate with HDD-750 IP Video Decoder, you can override the images.
- ► Equipped with RS-232 port: connect with BXB's UFO-2050 Conference MCU to control the camera.
- Equipped with RS-485 port: connect with BXB's HCK-700 Compact Camera Controller to control the camera.
- Equipped with RJ45 port: connect with BXB's FCS-6350 Conference MCU to remotely control the camera via Internet.



Hardware Specifications

Internet	RJ45 TCP/IP port x 1
Video Output	HDMI x 1
Audio Output	Φ3.5 linear source x 1
USB	USB2.0 x 2
RS-485 Control	RS-485 x 1
RS-232 Control	RS-232 x 1
N.O. Trigger	IN x 1



Physical Specifications

Dimensions	45*485*105 (mm)
(L x W x H)	
Weight	1.15KG (power supply
	not included)
Rack Mount 19"	1U



Power Supply

External Power	DC 5V-2A MAX
Supply	
Voltage/Frequency	110/220V
Power Consumption	10W
Weight of Power	0.1KG
Supply	

