

ATEO 4


Clevermount™ Design Loudspeaker

Features

- Patented Clevermount™ mounting system
- Stunning design of Loudspeaker and Bracket
- Installation & Connection in no-time
- 1" Dome tweeter & 4" Woofer
- 8 Ohm or 100 Volt (4 taps) connection
- High-Quality sound reproduction
- Horizontal & Vertical mounting
- Available in Black and White

Applications

- Residential applications
- Retail stores
- Clubs
- Pubs
- Restaurants
- ..



The ATEO 4 is the 4" version, with a 1" dome tweeter and a 4" Mid / Low frequency driver, ensuring a true to- nature, high-fidelity reproduction of music and speech.

It features a stunningly designed and elegant looking ABS housing which is fitted with High-Quality components. What makes this loudspeaker range so exceptional is the specially designed mounting bracket using the Clevermount™ technology, making the loudspeakers cabinet flow together with the mounting bracket providing a great ease for installing the loudspeaker in one good-looking entity.

The mounting and connection of the loudspeaker simply happens by attaching the included metal wall-plate to the desired location. When mounted, the wires must be connected to the desired terminal of the custom connection block. The desired power tap for 100 Volt or 8 Ohm can be selected by picking the right terminal. After this is done, only five seconds of work is left for clipping the loudspeaker onto the wall-plate, tightening the safety screw and you're ready to rock!

This way, it's really child's play to install a large number of loudspeakers in no-time. Even if you're working all alone while people are watching your fingers or when installing the speakers up high, when you're standing on a ladder.



▶Specifications

SYSTEM SPECIFICATIONS May payor	70 \\	
Max power	70 W	
RMS power	35 W	
Impedance	8 Ohm	
Line Transformer Power Taps	24 Watt / 417 Ohm	
	12 Watt / 833 Ohm	
	6 Watt / 1667 Ohm	
	3 Watt / 3333 Ohm	
Sensitivity 1W/1m	86 dB	
SPL max W / 1m @ 8 Ohm	101 dB	
SPL max W / 1m @ 100 V	100 dB	
Frequency response -3dB	100 Hz - 20 kHz	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	137 x 244 x 154 mm	
Weight net	2.05 Kg	
Drivers	1" HF Dome tweeter	
	4" MF / LF Woofer	
Connectors	6-pin custom Terminal Block	
Mounting bracket	Clevermount™	
Construction	ABS	
Front finish	Fine Perforated steel grill	
Incline angle	Left & Right	30°
	Bottom	30°
	Тор	5°
Colour	Black (RAL9005)	ATEO4/B
	White (RAL9010)	ATEO4/W
SHIPPING & ORDERING		
Packaging	Carton box (pair)	
Shipping weight & volume	5.00 Kg - 0.015 Cbm (2 pcs)	
Accessories included	Allen-key wrench	
	Screws and wall plugs	

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products

All Ateo series speakers are available in Black (/B) or White (/W).