## **BLS207**

## PROAB

## Speaker cable - 2 x 0.75 mm<sup>2</sup> - CCA



The BLS207 are double isolated loudspeaker cables composed of two twisted conductors in a flexible PVC outer jacket. The double isolated construction allows the cable being used in public address (100V) audio systems while the smooth and durable outer jacket offers a great installers convenience for easy installation and pulling.

The cable consist of individualy isolated conductors with a section of 2 x  $0.75~\text{mm}^2$  (18 AWG) which are composed out of stranded copper clad aluminum (CCA) wires. The stranding keeps the cable flexible and easy to handle while the copper clad aluminum construction results in a electrical performance between copper and aluminum cables. It combines the advantages from two sides, such as solderability, lower weight and lower material cost than bare copper with the higher conductivity and higher strength than pure aluminum. The cable composition is made of 75% aluminum with 25% copper.



INSTALL

Physical Characteristics				
Type of cable	2-Core speaker cable			
Inner conductor	CCA 24 x 0.20 mm			
Inner conductor section	0.75 mm²			
Number of conductors	2			
Insulation	PVC Ø 2.4 mm			
Insulation Colour	Red / Blue			
Conductor twisting	Yes			
Shielding	None			
Filling	None			
Separator	None			
Outer Jacket	PVC			
Outer Jacket Colour	Black / White			
Outer Jacket Dimensions	Ø 6.5 mm			
American Wire Gauge	18 AWG			
Conductor composition	75% AI - 25% Cu			


Standards & regulations		
RoHS2 compliant	According EU Directive 2011/65/EU	
Reach compliant	According EC 1907/2006	

Mechanical Characteristics				
Temperature range	fixed installation	-20° C till +80° C		
	flexible installation	-15° C till +60° C		
Bending radius	fixed installation	8 x cable Ø OD		
	flexible installation	10 x cable Ø OD		

Electrical Characteristics			
Max. conductor DC resistance	37 (Ω/Km)		
Dielectric strength	2 (KV/1min. DC)		
Voltage rating	300V		

Ordering & packaging			
BLS207/1	PVC, Black	100 meter plastic reel	
BLS207/3	PVC, Black	300 meter wooden reel	
BLS207W/1	PVC, White	100 meter plastic reel	
BLS207W/3	PVC, White	300 meter wooden reel	

## **Cross section**



Recommended accessories & connections			
Speaker connector	Procab	VCL4FC	
SpeakON connector	Neutrik	NL2FX/NL4FX	