

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet



# tasker® C280 – 2x0,22 mm<sup>2</sup> Balanced Microphone Cable



A	B	C	D
---	---	---	---

### CATEGORY APPLICATIONS

Balanced Microphone Cable (See Audio Catalogue)  
 Premade Audio Cables and Microphones.

- A:** Soft Blue PVC Sheath. Outer Diam. Ø 5,00 (±0,10) mm.
- B:** Shielding in O.F.C. red copper Spiral covering 100% + O.F.C. Tinned copper Drain Wire.
- C:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape. Core Insulation with a compact XLPE, colored one Red and one Transparent. Diam. Ø 1,20 (±0,20) mm.
- D:** O.F.C. red copper formation 28x0,10 mm. Nom. Cross section 2x0,22 mm<sup>2</sup>.

### MARKING

**tasker®** C280 2x0,22 PROFESSIONAL NOISELESS MICROPHONE CABLE FOR WIRING

### CUSTOM

This product is also available in **L.S.Z.H., PE, PUR**, with or without **Steel Armor**.

### Cable Properties

<b>Conductor Resistance</b>	79,15 Ω/Km
<b>Capacity Core/Core</b>	75 pF/mt
<b>Capacity Core/Shield</b>	160 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			