



**Applications:**  
U.T.P. – Unshielded Twisted Pairs cables cat. 5e UL/ETL verified for Local Area Network – LAN cables.

**tasker® C704** for fixed installations and **tasker® C705** for assembled cables or mobile installations.  
For **RJ 45 8 Pin** connectors.  
Standards: **EIA/TIA 568**.

**Characteristics:**

Conductors: **C704:** stiff wire in O.F.C. red copper  
**C705:** stranded in O.F.C. red copper

Cond. insulation: PE

Pair colours: White/blue-Blue, White/orange-Orange, White/green-Green, White/brown-Brown

Total tape: transparent Polyester (Pet)

External Sheath: PVC

Sheath colour: Grey



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C704	4x2	4 x 2 x 24 (0,22 mm <sup>2</sup> )	1x0,51	0,9		6,0	100	B	3,6
			7x0,15			0,9	6,0	300	B
C705	4x2	4 x 2 x 26 (0,14 mm <sup>2</sup> )	1x0,51	0,9		6,0	100	B	3,5
			7x0,15			0,9	6,0	300	B

Conductor Resistance Ω/Km ± 5%	Impedance Ω ± 5% 1 ÷ 100 MHz	Max Rated Voltage AC - V
90	100	49
140	100	49
		Operative Temperature °C
		-15 / +70



**Applications:**  
F.T.P. - Foiled Twisted Pairs cable cat. 5e UL/ETL verified for Local Area Network – LAN cables.  
For **RJ 45 8 Pin shielded** connectors  
Standards: **EIA/TIA 568**.

**Characteristics:**

Conductors: stiff wire in O.F.C. red copper

Cond. insulation: PE

Pair colours: White/blue-Blue, White/orange-Orange, White/green-Green, White/brown-Brown

Shield: Aluminium tape covering 100% stranded in tinned copper

Drain wire: stranded in tinned copper

External Sheath: PVC

Sheath colour: Grey



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C706	4x2	4 x 2 x 24 (0,22 mm <sup>2</sup> )	1x0,51	0,9		7,0	100	B	3,7
							7,0	300	B

Conductor Resistance Ω/Km ± 5%	Impedance Ω ± 5% 1 ÷ 100 MHz	Max Rated Voltage AC - V
90	100	49
		Operative Temperature °C
		-15 / +70