

FirestoP®

Halogen Free



OFC

PE

PVC



Connectors:

Panel connector RJ 45 8 Pin cat. 6A

tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool		
							mt.	Type	Kg.
C716	4x2	4 x 2 x 23 (0,25 mm ²)	1x0,57	1,0		6,7	305		

Conductor Resistance Ω/Km ± 5%	Impedance Ω ± 15% 1 ÷ 250 MHz	Max Rated Voltage AC - V
75	100	49
		Operative Temperature °C -15 / +70

Characteristics:

Conductors: stiff wire in O.F.C. red copper
 Cond. insulation: PE
 Pair colours: White/blue-Blue, White/orange-Orange, White/green-Green, White/brown-Brown
 Filler: Cross central filler in PE transparent Polyester (Pet)
 Total tape: Flame Retardant and LSZH PVC
 External Sheath: Grey
 Sheath colour: Grey

Product Description

U.T.P. (Unshielded Twisted Pairs) cable cat. 6A (Augmented) UL verified for Horizontal cabling in Local Area Network.
 Lan cable Cat. 6A for panel installation according with standards: **IEEE802.3an 10GBASE-T (10GBIT Ethernet™)**.
 Advised for Broadcast application and Network installation in: EDP centres, cinematographic studios, TV directions, Recording rooms, Theatres, public buildings and sport facilities, industrial environments and control centres in general.
 This cable is suitable for connection and supply of Cat. 6A equipments, Racks and Hub-LAN.

Descrizione Prodotto

U.T.P. (Unshielded Twisted Pairs) di cat. 6A (Augmented) certificato UL per cablaggio Orizzontale di reti locali (Local Area Network). Cavo LAN cat. 6A per installazione da pannello secondo le norme: **IEEE802.3an 10GBASE-T (10GBIT Ethernet™)**.
 Consigliato per applicazioni Broadcast ed installazioni Network in: centri EDP, studi cinematografici, regie televisive, sale di registrazione, teatri, edifici pubblici ed impianti sportivi, ambienti industriali e centri di controllo in genere.
 Questo cavo è adatto al collegamento di Armadi Racks, Hub-LAN ed apparecchi di Cat. 6A.