

EDC 1034 Digital Audio Interface WM 07/707 Hand-held MIC



Digital Audio Interface

- Digital signal transmission
- Has LINE IN/LINE OUT for receiving/delivering digital signal
- Connected with BXB WM/07/707 hand-held microphone
- Has a stereo earphone jack for recording
- Has an audio output jack for external flush mount hi-fi speaker
- Has volume adjustment of earphone and external flush mount hi-fi speaker
- **How to install:** Mounted into the desk or fixed to the arm chair

Hand-held Microphone

- Requires the BXB EDC 1034 Digital Audio Interface for system connection
- Uni-directional (Cardiod) microphone picks up desired audio and blocks out background audio
- Gooseneck microphone with illuminating red ring to indicate speaking status
- The illuminating red ring is flashing when request to speak
- Microphone has dust-proof and wind-proof to prevent explosion sound

TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ		
Sensitivity	≥ -50dB		
Total Harmonic distortion	≤ 0.1%		
S/N ratio	≥ 70dB		
Voltage	DC 12V~18V		
External Speaker	Unit Size	Model:	3" x 1.5"
	Capacity	WM-02D	2W
	Max. Sound Pressure		92dB
Speaking Indicator Lamp	Illustrated Red Ring Light		
Connection	1* 9P D type plug · for system link 9P cable (2.5M & 12M)		
AGC (Auto Gain Control)	45 ~ 0dB		
Earphone/REC jack	3.5Ø Stereo		
Height x Width x Depth	53.6 x 169.3 x 131.8 (mm)		
Weight	0.8 kg		
Material	Iron		

*The appearance and specifications of all item are subject to change without notice