

EDC 1051 Main Control Unit



- Has three (3) chain outputs for daisy connection, each link can be linked up to **25** units
- Can control up to 10 chairman units & **128** delegate units by extension power supply
- **System Auto-Test** functions when power on. When failed connection, the Red ring of light is flashing
 - **Multi-Conferencing Operating Modes:**
 - **NORMAL:** 1. Delegates have the ability to open their own mics. 2. No Request-to-speak
 - **VOICE (Auto-MIC Shut-Off):** 30/45 seconds without speaking, microphone will be automatically shut-off
 - **OVERRIDE:** 1. Delegates have the ability to open their mics. 2. When the maximum open mics is reached, delegate opens mic will take control of the current delegate, chairman is not affected
 - **CHAIRMAN:** 1. Delegates only have the ability to request-to-speak. 2. Chairman controls all delegate mic activation
 - **OPEN-MIC:** Numbers of Microphone push to talk simultaneously is up to 1-9, displayed on the main control front panel
- Main control unit and Chairman Unit controls all delegate mice activation and has the alarm sound when delegate-off
- Built-in sound-emission circuit to prevent echo and noise

TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
LINE IN :	-4dB~+6dB 10KΩ \geq (Balanced)
LINE OUT :	-4dB~+12dB 200Ω \geq (Balanced)
Sensitivity :	-60dB
T.H.D. :	\leq 0.5%
S/N Ratio :	\geq 90dB
Conference microphone connection :	D type 9P express port x 3 sets
MIC Input	4 set x 600Ω/6mV/-22dB
Line output	1 sets
Volume Indicators	5 LEDs
Power	AC110/220 , 50/60Hz , Power LED light
Height x Width x Depth	100 x 430 x 230 (mm)
Weight	10 (kg)