

FCS-6026

Flush-Mounted Delegate Unit



- Stylish Aluminum Extrusion
- Advanced Cat.5e Cable
- Max. 999 delegate units
- Electric condenser stem microphone
- Stereo earphone jack*1; Rec*1
- Volume Control
- 5 buttons for voting option
- BXB gooseneck microphones adopt DIN type plug preventing bad contact of the connector
- Pluggable gooseneck microphone
- Illuminated red light ring for easy mic on/ off identification
- Automatic system test function
- Stem length: 43/48/56/70 cm (17", 18.9", 22", 27.6")
- Digital parallel daisy-chain connection
- MIC auto-Off: 10-99 seconds

Information

BXB ELECTRONICS CO., LTD

TEL : +886(7)970-3838

FAX : +886(7) 970-3883

Email: bxb@bxb.tw

<http://www.bxb.tw>

6F.-1, No.288-5, Xinya Rd.,
Qianzhen Dist., Kaohsiung City
80673, Taiwan (R.O.C.)



TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
Sensitivity	≥ -50dB
Total Harmonic distortion	≤ 0.1%
S/N ratio	≥ 70dB
Voltage	DC 12V~18V
Connections	RJ-45 Jack*2 (2.5M/20M Cat.5e)
Auto Gain Control (AGC)	-45 ~ 0dB
Earphone jack	3.5Ø Stereo
REC jack	3.5Ø Stereo
Height x Width x Depth	32x 8 x 4.3 (cm)
Weight	800g w/o microphone
Material	Galvanized sheet steel
Surface	Aluminum extrusion