

# FCS 6350 Main Control Unit (W/ Voting, W/LCD)



- Has four(4) chain outputs for CAT5E cable loop-through, each can be linked up to **24** units
- Can control up to **10** chairman units & **999** delegate units by extension power supply
- Has **128x64pixels** digit LCD monitor display, the configurations can be set up and displayed
- **Multi-Conferencing Operating Modes:**
  - **NORMAL/OVERRIDE/CHAIRMAN**
  - **FIFO:** 1. Delegates have the ability to open their own mics 2. When the maximum open mics is reached, mics will go into request-to-speak queue
  - **OPEN-MIC:** Numbers of Microphone push to talk simultaneously is up to **1-30**
  - **VOICE (Auto-MIC Shut-Off):** **10-99** seconds without speaking, microphone will be automatically shut-off
- **System Auto-Test** functions when power on. When failed connection, the Red ring of light is flashing
- Main control unit and Chairman Unit controls all delegate mice activation and has the alarm sound when delegate-off
- Provides **RS-232** interface is supported with Creston or AMX wired or wireless touch screens
- Built-in Video Control Management Interface
  - Three (3) Phased Images Auto-Tracing Functionality: **BUTTON/VOICE/PRESET**
- Synchronized with BXB Authorized Conference Management Software
- Built-in sound-emission circuit to prevent echo and noise
- has a built-in DSP chip, which can adjust the audio output and sensitivity automatically
- TCP/IP network protocols, can login via **website** and also can use **iPhone/iPad APP** to control
- Pluggable USB interface for recording and music playing
- Digital Volume Adjustment
- Built-in Voting Functionality

## TECHNICAL SPECIFICATIONS

Frequency response :	50HZ~16KHZ( ±1dBV )
T.H.D. :	≤0.1%
S/N Ratio :	≥ 85dBV
Conference microphone connection :	CAT5E cable RJ-45 port x 4 sets
Ethernet Technology :	10 Mbps Ether Net
MIC Input (XLR+Ø6.3mm phone jack):	1 set x 600Ω/6mV/-20dB (Digital Control)
AUX Input (RCA) :	1 set x 20KΩ/300mV/0dB(Digital Control)
AUX OUT (RCA) :	-3dB~+12dB ≥ 200Ω ( Balanced )
Power	12~24VDC. Use Power adapter 24V, 5.2A, with fan.
Height x Width x Depth	100 x 430 x 280 (mm)
Weight	5.8 (kg)

\*The appearance and specifications of all item are subject to change without notice