

IED 1151/1150 GLOBALCOM® Servers

IED 1151 SERVER



Features

- Industrial Applications
- RAID 5 Configuration
- Redundant Power Supplies
- 2 Rack Spaces
- Windows Server 2012
- 8x8 or 16x16 Channel CobraNet® Card
- 3 Year On-Site Warranty

Specifications

Device	Dell® PowerEdge Server	Power Supply	Redundant Hot Plugable 495W
Operating System	Windows® Server 2012	Processors	1 Intel® Xeon E5-2400
Memory	8 GB	Power Supply (1+1)	495 Watts Efficiency 82% or better
Storage	3x500 GB RAID 5	Supply Voltage	100-240VAC 50/60Hz
Digital Audio	8 Input x 8 Output (standard) CobraNet® Card	Maximum Heat Dissipation	1908 BTU/Hr.
Video Output	2 VGA (1 Front, 1 Rear)	Operating Temp	10 C to 35 C at 10% to 80% Humidity + Expanded Operating Limits
Form Factor	2RU	Length	25.59" (650mm)
Network Interface	2 x 1GB Network Adapters 2 x 100MB Digital Audio Adapters	Width	17.09" (434mm)
USB	5 (2 Front, 2 Rear, 1 Internal)	Height	3.41" (86.6mm)

IED 1150 SERVER



Features

- Windows® 2012 Server
- 1 Rack Spaces
- 8x8 or 16x16 Channel CobraNet® Card
- 3 Year On-Site Warranty

Specifications

Device	Dell® PowerEdge Server	USB	5 (2 Front, 2 Rear, 1 Internal)
Operating System	Windows® Server 2012	Power Supply	Non-Redundant 250W (100V-240V)
Memory	8 GB	Processors	1 Intel® Core I3
Storage	500 GB	Efficiency	85% or better
Digital Audio	8 Input x 8 Output (standard) CobraNet® Card	Maximum Heat Dissipation	1040 BTU/Hr
Video Output	2 VGA (1 Front, 1 Rear)	Operating Temp	10C to 35C at 10% to 80% Humidity + Expanded Operating Limits
Form Factor	1RU	Length	15.39" (391mm)
Network Interface	2 x 1GB Network Adapters 2 x 100MB Digital Audio Adapters	Width	17.09" (434mm)
		Height	1.67" (42.4mm)