



# SMQ750

WaveDynamics™ Quad Channel Power Amplifier

## ► Features

- 4 x 750 Watt RMS output power
- Lightweight Class-D Amplifier
- Advanced DSP & Loudspeaker management
- Intuitive graphical interface on 2.5" LCD Display
- Pre-Loadable loudspeaker & set configurations
- Unmatched technology and affordability
- Flexible input and output configuration
- XLR & Terminal block source compatibility
- RS-232 control and USB loadable configurations

## ► Applications

- Clubs & pubs
- Restaurants & bars
- Warehouses & retail stores
- Public & office buildings
- Mobile applications
- ...



The SMA & SMQ amplifiers are defining a new standard in affordable amplification for both fixed and mobile audio installations. Their different channel configurations and availability in various output powers are providing an enormous flexibility for numerous applications.

The SMQ750 is the four channel version of this Class-D power amplifier with an output power of 750 Watt for each channel. The WaveDynamics™ DSP processor in combination with the 2.5" LCD display gives an unmatched user experience with intuitive functions overview for easy configuration.

Acoustics can be optimized using the filters selectable between Low / High & Band Pass and the 7-Band equalizer which both have adjustable frequencies and Q-factor. Other provided functions are delay and dynamic bass boost. These settings can be custom configured using the front panel of the amplifier, whereby access can be given in two different levels (User & Administrator) using password or USB-key protection. Loudspeaker protection is provided by an output power limiter whereby the maximum output power for every channel (in Watt) can be configured.

Configuration is made simple by the loudspeaker presets and full system configurations which can be selected from a library and uploaded with an USB flash drive. This ensures the best acoustical performance with a bullet-proof loudspeaker protection.

A great input flexibility and source compatibility is provided by the input selection matrix in combination with the XLR and terminal block signal connections. The outputs are performed using Speaker and Terminal block connections. System integration is made easy using the RS-232 control port.

## ► Specifications

SYSTEM SPECIFICATIONS		
RMS Power @ 4 Ohm Stereo	4 x 750 Watt	
RMS Power @ 8 Ohm Stereo	4 x 380 Watt	
RMS Power @ 8 Ohm Bridge	2 x 1500 Watt	
Frequency response	20 Hz - 20 kHz	
Signal to noise ratio	> 95 dB	
THD+N by 1 kHz (1/2 Rated Power)	< 0.05 %	
Crosstalk	> 70 dB	
Technology	Class - D	
Power supply	Switching mode	
Power supply range	230 ~ 240 V AC / 50 ~ 60 Hz	
Input Sensitivity	-19.5 dB ~ 27 dB	
Input Impedance	10 k Ohm balanced	
Common mode rejection ratio	70 dB	
Protection	Amplifier	DC Short-circuit Over heating Over load Signal limiting
	Loudspeaker	Output power limiter
	Access	User & Administrator level (Through password and USB-key protection)
Cooling system	Temperature controlled FAN (Infinitely)	
Operating temperature	0° ~ 40° at 95% Humidity	
Connectors	Input	XLR & 3-pin Terminal block (3.81 mm)
	Output	Speaker & 2-pin Terminal block (5.08 mm)
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	482 x 88 x 420 mm	
Weight net	8.40 Kg	
Mounting	19"	
Unit height	2 HE	
Construction	Steel	
Colour	Black	
SHIPPING & ORDERING		
Packaging	Carton box	
Shipping weight and volume	11.40 Kg - 0.046 Cbm	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		