



MILAN S.r.l.
Head Office - Export Dept.:
 20090 Cusago (MI) - Italy
 Viale Europa, 74
 Tel. +39 02 90394556 - 4158
 Fax. +39 02 90394551
 www.taskercables.com

**Ufficio Commerciale
 e Centro Distribuzione**
 20090 Cusago (MI) - Italia
 Viale Europa, 72 Strada F12
 Tel. +39 02 90390037 - 59
 Fax +39 02 90390049
 www.tasker.it

New tasker® Extra-Flex Digital Audio Multipair Cables

Extra Flexible Digital Audio Multipair Cables 110 Ω AES/EBU

Applications:

Extra Flexible Digital Audio Multipair Cables 110 Ω AES/EBU with smaller external diameters for fixed or mobile laying suitable for the realization of extensions or digital audio balanced multisoquets or for the connection of digital audio mixers and direction benches.



Characteristics:

Conductors: O.F.C. tinned copper
 Cond. Insulation: PEE (Foam PE)
 Pair colours: White, Red
 Total tapes: Polyester
 Drain wires: stranded in O.F.C. tinned copper
 Shields: Aluminium/Polyester tape covering 100% PVC
 Inner sheaths: PVC
 Insulat. colours: Black and numbered
 Total tape: Unweaved Polyester
 Total Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath diameter mm.	External Cable diameter mm.	Reel or Spool			Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
							Weight					
							mt.	Type	Kg.			
TSK 802	2x2	2x2x0,14 (26 AWG)	18x0,10	1,2	3,2	8,8	100	B		140	50	100
TSK 804	4x2	4x2x0,14 (26 AWG)	18x0,10	1,2	3,2	10,3	100	B		140	50	100
TSK 808	8x2	8x2x0,14 (26 AWG)	18x0,10	1,2	3,2	12,9	100	B		140	50	100
TSK 812	12x2	12x2x0,14 (26 AWG)	18x0,10	1,2	3,2	15,6	100	B		140	50	100
										Velocity of propagation %	Max rated Voltage AC - V	Operative Temperature °C.
										80	49	-15 / +70
Attenuation												
										Impedance Ω±3%	3 MHz. db/100mt.	8 MHz. db/100mt.
										110	7,5	11,0

**MILAN S.r.l. - tasker®
 TECHNICAL DEPARTMENT**