

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® TSK 1030 – 1x0,20 mm<sup>2</sup>

## Supreme Guitar Cable with Carbon Screen

  
**RoHS<sub>2</sub>**  
 2002/95/EC  
 2011/65/UE



**CATEGORY** Guitar Cable (See Audio Catalogue)  
**APPLICATIONS** Premade cables for instrumental cable like Guitar, Bass and Keyboards

- A:** Nylon braid external cover, with Outer cable Diam. Ø 4,60 (±0,20) mm.
- B:** Black Soft PVC Sheath. Diam. Ø 3,40 (±0,20) mm.
- C:** Double Shielding with two O.F.C. red copper opposing spirals covering 100%.
- D:** Third shielding with conductive carbon screen.
- E:** Transparent PE insulation with outside diameter Ø: 1,80 (±0,20) mm.
- F:** O.F.C. stranded red copper formation 41x0,08 mm.  
Nom. Cross section 1x 0,20 mm<sup>2</sup>.

**MARKING** tasker® TSK1030 1x0,20 mm<sup>2</sup> O.F.C. Triple Shield Supreme Guitar Cable.  
**CUSTOM PRODUCTION** This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

### Cable Properties

<b>Conductor Resistance</b>	79,15 Ω/km
<b>Capacitance</b>	110 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			