

DIMIC1

ALL CALL DIGITAL
PAGING STATION



PERFECT COMMUNICATION

In most applications an all call microphone is indispensable to guarantee a good communication. Apart's DIMIC1 microphone is especially designed to function in a plug and play way with our electronics and makes sure that your message will be heard loud and clear throughout the entire office.

DIMIC1 is an all call digital paging station for use with AUDIOCONTROL12.8 that is easy to configure via the host's graphical installer interface.

- For use with AUDIOCONTROL12.8
- Inconspicuous and elegant design
- Remarkable sound quality
- Flexible microphone stem
- Unidirectional condenser microphone
- Speech-optimized sound processing
- Push-to-talk button and multicolor paging status LED
- All zone selection button
- Universal configuration of push buttons

TECHNICAL SPECIFICATIONS

Dimensions base (w x d x h)	110 x 240 x 58 mm
Cut-out dimensions	85 x 230 mm
Mic stem length including mic and windscreen	395 mm
Weight	600 g
Power supply	12 - 24 VDC/75 mA max
Nominal sensitivity	85 dB SPL
Maximum sound pressure level	> 110 dB SPL
Nominal output level	775 mV
THD	typical < 0.5%
Frequency response -3 dB	220 - 20000 Hz (speech filter)
Lo-cut	220 Hz, 6 dB/oct
Accessories	Manual, CAT5 cable 5m, microphone, windscreen