





EXCELLENT MUSIC QUALITY

OVO5P is an active speaker set that consists of an active and a passive loudspeaker. A speaker set with excellent musical quality, crystal clear voice reproduction and high sound level with 2×20 W output power.

The OVO5P bass reflex speaker has a 5 ¼ inch woofer and a 1" soft dome tweeter. You have volume control options and separate bass and treble control.

The stereo mini-jack input of the OVO5P with increased sensitivity allows you to connect a laptop, iPod or MP3-player. Also available on the OVO5P is a stereo RCA/ Cinch input for unbalanced line level signals.

The Apart OVO5P has been designed for a wide range of indoor installation applications such as class rooms, boardrooms, hotel rooms or many other indoor applications where a stylish but budget friendly loudspeaker is needed.

OVO5P is available in black or white.

APart OVO5P has plenty of wall mounting possibilities due to the painted metal speaker brackets that have various possible installing angles. Thanks to the floor standing bracket, OVO5P can be placed freestanding too, for example on your desk.

TECHNICAL SPECIFICATIONS

System setup2-way bass reflex speaker 5¼ inch coated paper woofer 1 inch soft dome tweeterInput sensitivity / impedanceRCA stereo: 500 mV, 10 KΩ Mini-jack: 150 mV, 2.7 KΩTone controlBass: +/- 12 dB at 80 Hz Treble: +/- 12 dB at 12 KHzSystem performance2 x 20 Watts RMSFrequency range50 Hz – 20 KHzTHD< 0.03 % at full power -6 dB	Speaker type	Active speaker set (2 speakers)
anceMini-jack: 150 mV , $2.7 \text{ K}\Omega$ Tone controlBass: +/- 12 dB at 80 Hz Treble: +/- 12 dB at 12 KHz System performance $2 \times 20 \text{ Watts RMS}$ Frequency range $50 \text{ Hz} - 20 \text{ KHz}$ THD $< 0.03 \%$ at full power -6 dB	System setup	5¼ inch coated paper woofer
Treble: +/- 12 dB at 12 KHz System performance 2 x 20 Watts RMS Frequency range 50 Hz – 20 KHz THD < 0.03 % at full power -6 dB		•
Frequency range 50 Hz – 20 KHz THD < 0.03 % at full power -6 dB	Tone control	
THD < 0.03 % at full power -6 dB	System performance	2 x 20 Watts RMS
() () () () () () () () () ()	Frequency range	50 Hz – 20 KHz
S/N ratio > 90 dB	THD	< 0.03 % at full power -6 dB
	C/N watio	> 00 dP

Channel separation	70 dB
AC supply voltage	230 VAC + 10 %, 50-60 Hz
Max power consumption	50 VA
Idle power consumption	10 VA
Speaker construction	ABS molded cabinet
Dimensions (H x W x D)	260 x 160 180 mm
Weight (pair)	5.3 kg
Shipping weight	6.7 Kg
Included accessories	brackets, manual, power cord, speaker wire