



ALTI4

2-way 4" pendant speaker

Highlights:

- Ceiling suspension
- Innovative & unique design
- Dual Grippler™ locking system
- Wide opening angle
- Suspension cable with dual steel core
- Ceiling cable cover
- Rotary switch for 6W, 12W, 24W and 16 Ohm tapings

"Pure sound, hanging around."

The ALTI4 is a 2-way pendant loudspeaker featuring a 4" driver combination with a coaxially mounted 1" soft dome tweeter and is fitted with a phase plug for excellent off-axis performance.

The 2-way combination with a high-quality polypropylene enclosure and acoustic engineering craftsmanship guarantees premium performance for demanding applications. A continuous power handling of 30 Watt (RMS) and maximum power handling of 60 Watt is achieved. Connections are made through a terminal block connector behind the rear cover, accompanied with a power tap selector switch for the tapping of a 70V/100V line transformer with tapings for 24W, 12W, 6W and a 16 Ohm bypass connection.

Applications:


- Bars, restaurants
- Retail
- Education
- Public facilities
- Corporate spaces
- Sport facilities



Impedance:



Voltage:



System specifications:


Max. Power		60 W
RMS Power		30 W
Speaker type		2-way coaxial
Drivers		4"
Impedance		16 Ω
Line Transformer Tappings	1	208 Ω - 100 V / Not used - 70 V / 24 W
	2	417 Ω - 100 V / 24 W - 70 V / 12 W
	3	833 Ω - 100 V / 12 W - 70 V / 6 W
	4	1667 Ω - 100 V / 6 W - 70 V / 3 W
Dispersion	Conical	165° (average 500 Hz to 5 kHz @ -6 dB)
Connectors		4-pin Euro Terminal Block
Sensitivity (1W/1m)		80 dB
Sound Pressure (Max. W/1m)	@ 16 Ω	95.1 dB
Frequency	Range (-10 dB)	65 Hz - 20 kHz
	Response (\pm 3 dB)	85 Hz - 20 kHz

Product Features:


Dimensions		170 x 223 mm (\varnothing x H)
Connection cable length		3.5 m
Construction		Polypropylene
Front finish		Aluminium grill
Mounting & handling		Dual snap hook and dual Gripple™ hanger
Accessories	Included	Connection cable with dual copper and dual steel cores 2 Gripple™ hangers

Acoustical data graphs:


Horizontal Polars:




Vertical Polars:




Sensitivity:






Beamwidth (-3dB):



Directivity index:





ALT14

Product description:

2-WAY 4" PENDANT SPEAKER 24W -
70V/100V & 16 OHM

Weight:

TBA

Outer dimensions:
(w x h x d)

$\text{Ø}170 \times 220$

Unit height:

N/A