SoundWare XS 5.1

play together. play smart.



High Performance Surround Sound Speaker System

The SoundWare XS 5.1 Loudspeaker System is an ultra-compact 5.1 speaker system that brings a new level of style and substance to the fast-growing surround sound home entertainment category. It allows users to enjoy rich, room-filling surround sound with their home entertainment systems, while complementing virtually any décor in a stylish yet subtle (even virtually unnoticeable, if desired) manner.

The system's five ultra-compact and stylish SoundWare XS satellites are real two-way speakers (unlike many competitors).

Each features a high-performance 2½-inch (64mm) woofer and a ½-inch (13mm) tweeter. The contoured-rectangle subwoofer, colored to match the satellites in either black or white, features a 100-watt (250 watts peak) amplifier and 8-inch (203mm) driver.

Wall brackets are included for easy installation of all five satellite speakers.











SoundWare XS 5.1









any angle any surface anywhere

2-way Satellite Speakers:

- SoundWare XS satellite speakers are incredibly small yet provide big, high performance sound
- Speakers sit or mount at any angle for maximum placement flexibility
- Included articulating mounting brackets allow speakers to be positioned at any angle

What it means to be from Boston.

Many manufacturers design their products around third-party, off-the-shelf parts. Boston Acoustics engineers every component of every system to meet the highest performance standards (our own). Of course, performance is only one measure of value. So we're careful to build all our products with strict attention to everything from the choice of materials to the details of fit and finish. It's how we've been exceeding the expectations of serious listeners for more than thirty years.

Specifications

	Satellite	Subwoofer
Frequency Response	150Hz – 20kHz	40 - 150Hz
Recommended Amp Power	10 – 100 watts	
Nominal Impedance	8 ohms	
Sensitivity	85dB [SPL/2.8v at 1m]	
Woofer	2½" (64mm)	8" (203mm)
Tweeter	½" (13mm)	
Crossover Frequency	5kHz	60Hz -180Hz 24dB/
		octave lowpass
Net Weight	1 lb (.5kg)	20 lbs (9kg)
Dimensions (H x W x D)	$4^{5}/_{16} \times 4^{1}/_{2} \times 3^{3}/_{4}$	121/4 x 113/16 x 159/16"
	(108 x 113 x 94mm)	(310 x 284 x 395mm)

8" 100-watt Powered Subwoofer:

- Graphite injected polymer woofer utilizes Deep Channel® Design (DCD) for more bass from less amplifier power
- BassTrac® circuitry for tight, distortion-free bass at all output levels
- 100-watt (250 watts Peak) amplifier for powerful low frequency reproduction
- · Acoustically tuned port for improved bass output



